

Advantage Cushion Turf

Description

Advantage Cushion Turf is a heavy bodied elastomeric coating fortified with fine rubber aggregate for a long-lasting, high-quality resilient surface. Advantage Cushion Turf is supplied in concentrated form and diluted with water prior to application. Advantage Cushion Turf is designed as an underlayment course for the Advantage Color System and can be applied over new or suitable old surfaces.

Uses

Advantage Cushion Turf is applied over asphalt and concrete surfaces to provide added player comfort and reduced muscle fatigue.

Surface Preparation

New asphalt pavements should cure a minimum of 14-21 days prior to any coating application. New concrete surfaces should cure 28 days prior to any coating application. **(When installing over concrete surfaces, the concrete must be installed with a suitable vapor barrier and without concrete curing compounds.)** New and old surfaces should be thoroughly cleaned with compressed air and free from oil, grease, dirt and other foreign matter. Embedded dirt should be brushed thoroughly prior to any coating application. Grease and oil spots should be primed with an approved oil spot primer. See Advantage Specifications for complete information.

Mix Design

The following mix is recommended for average pavement conditions.
Advantage Cushion Turf ... 55 gallons
Water ... 22-24 gallons

When ordering Advantage Cushion Turf, figure 10-12 square yards per gallon of concentrated material for each coat of cushion.

An optimum cushion system consists of three applications of Advantage Cushion Base and two applications of Advantage Cushion Turf. An absolute minimum cushion system should consist of two applications of Advantage Cushion Base and one application of Advantage Cushion Turf.

Application

Advantage Cushion Turf is applied with a 50 durometer rubber squeegee. Care should be taken not to leave ridges. When the first application has dried, the second application shall be made at 90 degrees to the first application.

Clean-up

Rinse tools with water soon after using. Dried material can be removed with an approved solvent.

Shelf Life

Approximately 9 months

Physical Properties

Weight/Gallon ... 9.2 lbs. per gallon
Drying Time ... Touch: 2 hour
Firm: 48 hours
Application Temperature ... 50° F and rising

Precautions

Keep from freezing. Harmful if swallowed. Read material safety data sheets.

Shipping Weight

55 gallon drum ... 545 lbs.

Warranty: This product is guaranteed with respect to uniformity and quality. Since its use is beyond the control of the manufacturer, liability for damage shall in no case exceed the purchase price on the quantity of material used. Warranty is void on multi-coat applications if material made by other manufacturers is used with this product.

phone: 800.821.8549

816.923.4325

fax: 816.923.6472

web: chooseadvantage.com

► 5201 Brighton

Kansas City, Missouri 64130

Manufactured by Vance Bros Inc